



# PRO1 SUBMITTAL SHEET

Job Name: \_\_\_\_\_ Location: \_\_\_\_\_ Date: \_\_\_\_\_

Purchaser: \_\_\_\_\_ Installer: \_\_\_\_\_

Submitted to: \_\_\_\_\_ For: ☐ RNC ☐ R&R ☐ Commercial

## MODEL T751

### Universal

Up to 2 Heat 2 Cool Conventional  
Up to 3 Heat 2 Cool Heat Pump  
Battery or Hardwire  
Non-Programmable



### This model features:

- 7 sq. inch display
- Blue backlight
- Glow in the dark light button
- Easy access battery compartment
- Universal subbase
- Simple private label badge system
- Setpoint limits
- Electric or gas configurable
- Mounts on wall or junction box
- • Auto changeover (\*Not available in PTAC mode)
- PTAC capable
- 5 Year Warranty
- 5 minute compressor delay protection (selectable on or off)
- Customizable staging logic
- Separate heating and cooling swing (cycle rate) adjustments
- Battery or 24V power
- Room temperature calibration adjustments
- Easy wire color coded terminal blocks
- Three speed fan

### Specifications:

|                    |                                                                                                               |
|--------------------|---------------------------------------------------------------------------------------------------------------|
| Application        | Up to 2 Heat 2 Cool Conventional, 3 Heat 2 Cool Heat Pump                                                     |
| Programmability    | Non-Programmable                                                                                              |
| System Switch      | Cool - Off - Heat- Auto                                                                                       |
| Display Range      | 41°F to 95°F (5°C to 35°C)                                                                                    |
| Control Range      | 44°F to 90°F (7°C to 32°C)                                                                                    |
| Display Accuracy   | +/- 1°F                                                                                                       |
| Heat Swing         | Adjustable from 0.2°F to 2.0°F                                                                                |
| Cool Swing         | Adjustable from 0.2°F to 2.0°F                                                                                |
| Terminals          | Rc, Rh, G, Y, Y2, C, O, B, W/E, W2                                                                            |
| Load Rating        | 1 amp per terminal, 1.5 amp maximum all terminals combined                                                    |
| Power Source       | 18 to 30 VAC, NEC Class II, 50/60 Hz for hardwire (common wire)<br>Battery power from 2 AA Alkaline batteries |
| Operating Ambient  | 32°F to +105°F (0°C to +41°C)                                                                                 |
| Operating Humidity | 90% non-condensing maximum                                                                                    |
| Mounting           | Wall or Junction Box                                                                                          |
| Dimensions         | 4.7"W x 4.4"H x 0.8"D (119mm W x 112mm H x 20mm D)                                                            |
| Warranty           | 5 year warranty                                                                                               |